## BLACK BEAUTY 305

## MONO BLOCK VACUUM TUBE AMPLIFIERS VTA305M

Number of Line Inputs 1

Input Impedance 100K Ohms

Input Stage 12AX7 current sourced low noise valve

Pre-Driver Stage 12AT7 long tailed high gain balanced pair

Automatic DC Restoration 6AL5

Nominal Voltage Gain 30dB (into 8 ohms)

Output Stage Configuration 3 complimentary sets of KT-120's in a push-pull configuration (6 total)

Regulated Screen Supply Voltage 390V

Output Tube Plate Voltage 785V

Output Tube Idle Power Less than 14W each

Bias Adjustment Rear panel pot, front panel meter, "Set and Forget"

Rated Power 305 watts/8 ohms, 330 watts/4 ohms, 290 watts/2 ohms

Noise Better than 110dB A weighted referenced into 305 watts

Hum -100dB

Frequency Response 2 Hz to 85 kHz (-3dB)

Full Power Bandwidth 24 Hz to 28 kHz without filters

Feedback Control Switch 20dB for Classic Amplifier Sound, 11dB for Contemporary Amplifier Sound

Distortion Less than 0.5%

Output Transformer Interleaved windings, super wideband low leakage inductance design

Generator Source Impedance 1.6 ohms

Speaker Outputs 2, 4 and 8 ohm terminals

Built in Output Tube Tester Yes

Construction Method Point-to-point hand wired axial and radial leaded components with star grounds and no

circuit board traces or de-plugable connectors

Components High reliability wire wound and metal film resistors, metal polyester capacitors in the audio

Bob Carula MONO BLOCK

signal paths

Dimensions/Weight 14" deep x 12" wide x 7.2" tall, 43 lbs per chassis

Color Gloss Black with a silver fleck and brushed silver trim (may be ordered in Cherry)

Country of Origin USA

Warranty Amps 7 Years, Tubes 1 Year

